

Sale Model			106050
Electrical	Power supply	V-Ph-Hz	208/230V-1Ph-60Hz
	Minimum Circuit Amp	A	12.0
	Max. Overcurrent Protection	A	20
Cooling	Capacity	Btu/h	18000
	SEER	Btu/h.W	14
	EER	Btu/h.W	12.2
Compressor	Model		ZP14K5E-PFV-130
	Type/Brand		Scroll/Copeland
	Power Supply	V-Ph-Hz	208/230V-1Ph-60Hz
	Capacitor	uF	30
	RLA-LRA	A	9-46
Outdoor fan motor	Model		YDK85-6L
	Type		PSC
	Capacitor	uF	6
	Rated RPM	r/min	1075
	Rated HP		1/8
	FLA		0.7
Outdoor fan	Material		Metal
	Type		Axial flow fan
	Diameter	inch	17-3/4
	Height	inch	4-5/16
Outdoor coil	Type		
	Tube and fin		
	Rows-F.P.I		2-21
Outdoor air flow		m3/h	2688
		CFM	1581
Outdoor sound level(sound pressure level)		dB(A)	62
Refrigerant system	Factory charge(R410A)	lbs-oz	2-21
	Liquid side/ Suction side	inch	3/8 3/4
	Refrigerant control		/
Outdoor unit	Dimension(W*H*D)	mm	554X633X554
		inch	21-7/8×24-15/16×21-7/8
	Packing (W*H*D)	mm	582X667X582
		inch	22-9/10x26-1/4x22-9/10
	Net/Gross weight	Kg	55/58
		lbs	121/128
Shipping per STD40HQ			320