



CARBON MONOXIDE ALARM

10-YEAR NEVER-REPLACE BATTERY

DETECT SERIES | MODEL COB10

ALARMS AT DANGEROUS LEVELS OF CO

Notifies you when it's time to evacuate to fresh air outside.

NO LOW BATTERY CHIRPS AT NIGHT

Alarm senses when it's dark, so you won't be disturbed by alerts that aren't critical.



*Images are representative only.
Actual product may vary slightly.*



Conforms To
Standard
UL 2034

Description

Find peace of mind with the latest CO detection from North America's #1 home fire safety brand.* The Kidde Carbon Monoxide Alarm model COB10 alarms at dangerous levels of CO to help give you more time to get out safely. Powered by a 10-year never-replace battery,** this portable alarm can be placed on walls or countertops. Equipped with end-of-life notifications, it beeps to remind you it's time to replace it 10 years after it's powered. And it's comprehensively tested and designed to the latest UL standard for safety and reliability.

Alarm Warnings – Featuring multi-color LEDs

CO Alarm: Red LED blinks 4 times every 5 sec in sync with 4 short beeps. After 4 mins, the CO alarm pattern will occur every 60 sec.

CO Alarm Memory: Red LED blinks twice every 15 sec if CO has been detected for up to 7 days.

End of Unit Life: Amber LED blinks twice every 60 sec in sync with 2 chirps.

Low Battery Alert: Amber LED blinks every 6 sec + single chirp every 60 sec.

CO Fault: Amber LED blinks twice every 60 sec + 3 chirps every 60 sec.

Additional Features & Benefits

- **End-of-Life Notifications** – Eliminate the guesswork with replacement reminders after 10 years.
- **10-Year Never-Replace Battery**** – No battery replacements or chirps.

Installation of Alarm

This model meets the latest carbon monoxide standards. Industry experts recommend a CO alarm be installed on each level of the home — ideally on any level with fuel-burning appliances and outside of sleeping areas. See User Guide for more location information and additional instructions.

Architectural & Engineering Specifications

▲ WARNING: This product is intended for use in indoor residential locations. It is not designed to measure compliance with Occupational Safety and Health Administration (OSHA) commercial or industrial standards. This device is designed to help protect individuals from acute effects of carbon monoxide exposure. It will not fully safeguard individuals with specific medical conditions. If in doubt, consult a medical practitioner. Individuals with medical problems may consider using warning devices which provide audible and visual signals for carbon monoxide concentrations under 30 ppm.

- CO sensor alarm times:
- 70 ppm: 60-240 min
 - 150 ppm: 10-50 min
 - 400 ppm: 4-15 min

The alarm shall include a test button that will electronically simulate the presence of carbon monoxide and cause the unit to go into alarm. This sequence tests the unit’s electronics to ensure proper operation. The unit shall incorporate three LED colors. During normal or standby operation, a green LED will blink approximately every 60 seconds. An amber LED will indicate fault conditions. A red LED will blink in sync with the carbon monoxide alarm pattern, and will also indicate alarm memory. The unit shall include the HUSH™ feature that silences an alarm temporarily if a nuisance alarm condition occurs. At the date of manufacture, the unit shall at a minimum meet the requirements of UL 2034, NFPA 72, NFPA 101 (one- and two-family dwellings), Federal Housing Authority (FHA), Housing and Urban Development (HUD), and California State Fire Marshal (CSFM).

Technical Specifications

Model:	COB10
Power Source:	10-year never-replace battery
CO Sensor:	Electrochemical
Audio Alarm:	85 dB at 10 ft
Temperature Range:	40 °F (4.4 °C) to 100 °F (37.8 °C)
Humidity Range:	10 to 95% relative humidity (RH), non-condensing
Size:	5.14" W x 1.4" D x 2.83" H
Weight:	0.28 lb
Wiring:	N/A
Interconnects:	N/A
Warranty:	10-Year Limited Warranty on alarm (battery included)
Replacement Batteries:	N/A

Ordering Information

Ordering Number	UPC	GTIN	Pack Config.	Pack Qty	Case Dimensions (D x W x H inches)	Case Weight (lbs)	Cartons/Pallet
21033775	047871337750	10047871337757	Box	6	14.02 x 6.3 x 6.06	3.35	108

