

Straight Blade Devices 125V, 2 Pole, 3 Wire Grounding USB Charger Outlets

HUBBELL

Features

- Four USB ports 5 Amp, 2 Type A and 2 Type-C USB, 5V DC, class 2.0
- Fast charge enabled modulates up to 9 volts
- Switch activated port door; when open enables power; when closed, all power is switched off, for a “zero” no-load draw
- Green LED indicator to show USB power available
- Compatible with USB 1.1/2.0/3.0 devices, including Apple® products

Ordering Information

Description	Device Color	UPC	Catalog Number
USB Charger 4 Port Outlet. 2 Type A, 2 Type-C USB Ports. 5 Amp, up to 9 Volt DC, Style Line Decorator	White	883778308987	USB4ACW



Listings

cULus
FCC Approved
Compatible with USB 1.1/2.0/3.0 Devices

Specifications

Face	Reinforced Thermoplastic
Base	Reinforced Thermoplastic
LED	Green Indicator
Mounting Strap	Galvanized steel
Auto Self-grounding staple	Stainless steel
Mounting Screws	Zinc plated steel
Terminal Screws	Plated steel
USB Port	Stainless Steel

Performance

Electrical

Current Interrupting Receptacle certified for current interrupting at full rated current

Dielectric Voltage Withstands 1,500V minimum

Mechanical

Product Identification Ratings are a permanent part of the device

Terminal Accommodation #14-#10 AWG copper stranded or solid conductor only

Terminal Identification Terminals identified in accordance with UL 498 and CSA

USB Port Stainless steel Rated for 10,000 plug insertions and removal

Environmental

Flammability UL 94V-2

Operating Temperature Maximum continuous 75°C; minimum -40°C (w/o impact)

Resources

Installation Instructions
Sales Drawing
eCatalog

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

