

52" CEILING FAN with LED LIGHT KIT

162098

Features

- 3-speed reversible
- Pre-assembled, quick connect design
- 12" alabaster glass light shade
- Control by pull chain switch
- Rated for indoor use only
- Suitable for dry locations only
- ETL approved, confirms to UL STD 507



Specifications

Item #	162098
Diameter	52"
Motor Size	AC 153 x 12 mm
Downrod	4"
Blade Pitch	12°
Voltage	120V 60Hz
Finish	Oil Rubbed Bronze
Product N.W.	15.20 lbs.

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$11

Airflow

2,822

Cubic Feet Per Minute

▼

\$3

\$34

Cost Range of Similar Models (19" – 84")

• Based on 12 cents per kWh and 6.4 hours use per day
 • Your cost depends on rates and use
 • Energy Use: 38 Watts

• The higher the airflow, the more air the fan will move
 • Airflow Efficiency: 75 Cubic Feet Per Minute Per Watt

Airflow Average (CFM)	Airflow High/Low Speed (CFM)	Electricity Use	Airflow Efficiency
2822 Cubic Feet Per Minute	3846/1661 Cubic Feet Per Minute	65 Max watts (Excludes Lights)	75 Cubic Feet Per Minute Per Watt

Lighting



Light Bulb **Includes (2) 9W A19 LED Bulbs**

Lamp Base **Medium**

CCT **3000K**

Lumen **2*800lm**

Voltage **120V 60Hz**

Dimmable **No**

Blades

QTY **5**

Side 1 **Medium oak**

Side 2 **Mahogany**

Size **523 x 138 x 120mm**

Reversible **Yes**

