

# DURALIFE

### **High Gloss Floor Finish**

Clear, durable floor finish and sealer designed specifically for low maintenance programs. Economical formula ideal for low maintenance budgets, including applications such as schools, plants, factories, retail and more. Spray buff or scrub and recoat to maintain. Formulated for facilities that buff once per week or less. For use on resilient flooring and concrete.



## 352071

#### **PRODUCT INFORMATION:**

- · Sealer and finisher
- · Resists scuffs and marks
- Exceptional durability
- Ideal for vinyl floors

рН	8.3 - 8.9
Form	Liquid
Fragrance	Acrid
Color	White
Packaged	4/1 gl Case

#### **DIRECTIONS FOR USE:**

**INITIAL APPLICATION:** Completely strip all old wax or finish. Be careful to follow the "Directions for Use" for the selected stripper. Remove the stripping solution and follow with a thorough detail mop. Allow floor to completely dry. Repeat if necessary. Floor must be clean, dry and free of all residue. Apply 1 or 2 even coats of sealer (optional, based on condition of floor), and let dry. Apply finish in uniform, thin coats. Allow each coat to dry for 20 to 30 minutes, or until surface is completely dry to the touch, before applying additional coats. Allow an extra 10 minutes drying time for each additional coat. Total of 4-5 coats of finish are recommended. **ROUTINE MAINTENANCE:** Sweep large debris and remove. Dust mop to remove dry soil, then damp mop or automatic scrub with a neutral cleaner. Buff or burnish the floor as desired. Use of a cleaner/restorer is recommended to extend time between top scrub and recoating. **INTERIM MAINTENANCE:** Sweep large debris and remove. Dust mop to remove dry soil, then damp mop or automatic scrub with a neutral cleaner. Buff or burnish the floor as desired. Use of a cleaner/restorer is recommended to extend time between top scrub and recoating. **INTERIM MAINTENANCE:** Sweep large debris and remove. Dust mop to remove dry soil, then damp mop or automatic scrub with a neutral cleaner. Top scrub with top scrub cleaner and recommended floor pad to remove top soiled layers of finish. Floor must be clean, dry and free of all residue. Apply 1-2 coats of finish as directed under "Initial Application" on this label. **KEEP FROM FREEZING** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection and face protection.

#### **IMPORTANT SAFETY INFORMATION:**



DANGER May damage fertility or the unborn child.

Store locked up. Dispose of contents and container in accordance with local, regional, national and international regulations.

FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. FOR INDUSTRIAL & INSTITUTIONAL USE



Chadwell Supply 4907 Kearney Blvd. Tampa, FL 33619 (888) 341-2423 www.chadwellsupply.com



Chemtrec Emergency Response (800) 424-9300