800.364.7681



www.DOGIPOT.com

DOGIPOT® PET STATION (ITEM #1003-L)

SPECIFICATION, INSTALLATION AND OPERATION SHEET



YOUR ALUMINUM DOGIPOT® PET STATION INCLUDES:

- Aluminum **DOGIPOT**® Pet Sign, with mounting hardware (two (2) 2¼" X ¼" tap bolts, washers and locknuts)
- Aluminum **DOGIPOT®** JUNIOR Bag Dispenser (ITEM #1002-2), with mounting hardware (two (2) 2½" X ¼" bolts, washers and locknuts)
- Two (2) keys for Dispenser locking front access panel
- Two (2) rolls of DOGIPOT® Smart Litter Pick Up Bags™ (ITEM #1402) (200 count per roll), installed in DOGIPOT® JUNIOR Bag Dispenser
- 10 Gallon Steel Trash Receptacle (ITEM #1206-L) with attachable lid and trash liner bag retainer bands, with mounting hardware (one (1) 2½" x ¼" and (1) 2¾" x ¼" bolts, washers and locknuts)
- One (1) box **DOGIPOT®** Smart Liner Trash Bags™ (ITEM #1404) (50 count)

SEPARATE SHIPPING BOX

• 2" x 2" x 4' - 8' Galvanized Steel Telescopic Mounting Post, with installation hardware (two (2) carriage bolts $(2\frac{1}{2}$ " x 5/16"), washers and locknuts)

PLEASE CHECK THE ABOVE INVENTORY AND CALL YOUR DISTRIBUTOR IF ANY PARTS ARE MISSING.

INSTALLATION AND OPERATION INSTRUCTIONS

- 1. Select a good visible spot in your community or park where you want to install the Aluminum **DOGIPOT®** Pet Station.
- 2. Prior to installation, remove the 1%" x 1%" x 4' portion of the mounting post from the 2" x 2" x 4' portion of the mounting post before cementing. Insert the larger portion of the mounting post (2" x 2" x 4') approximately 14"

into an 18" deep by 8" diameter hole filled with a 40 lb. bag of "ready to use" concrete mix. To stabilize the post while cementing, place a rod, bolt or other device through the two bottom holes, prior to inserting into the ground and cementing. Level the post in a straight vertical position and let concrete dry for at least 12 hours.

- 3. After the concrete is dry, insert the smaller portion of the post (1¾" x 1¾" x 4′) into the larger cemented portion of the post (2′ x 2′ x 4′) until the the first 4 holes are lined up between the two posts. Use two (2) carriage bolts, washers and locknuts to fix the telescopic post in position. , the upper bolt in the top overlapping hole, pointing from right to left and the lower bolt in the bottom overlapping hole, pointing from front to back. The total height above ground with both post parts should now be approximately 6″6″.
- 4. Start by installing the **DOGIPOT®** Pet Sign on top of the 1¾" post, with the upper hole matching the most upper hole in the square post using the enclosed 2¼" bolts, washers and locknuts. Continue installing the Aluminum **DOGIPOT®** JUNIOR Bag Dispenser according to the mounting instruction enclosed with the Dispenser, ensuring that he upper edge of the Dispenser is approximately **1" below** the lower edge of the **DOGIPOT®** Pet Sign.
- 5. Install the Steel **DOGIPOT®** Trash Receptacle through the pre-drilled top oval holes in the back wall of the receptacle and through the square post with the remaining bolts, washers and locknuts, using the 2¾ bolt on top and the 2½ bolt below. **The upper edge of the trash receptacle must be approximately 12½" below the lower end of your Aluminum DOGIPOT® JUNIOR Bag Dispenser so that the lid may completely open.** The upper back wall of the trash receptacle is supposed to touch the head of the lower post carriage bolt, which creates some space between the post and the receptacle, allowing the receptacle lid to open from left to right, without touching the post.
- 6. Insert one of the enclosed **DOGIPOT®** Smart Liner Trash Bags™ into the trash receptacle, folding it over the interior retainer bands. As with any powder coated steel product constantly exposed to the elements, proper installation and general maintenance will help prevent and minimize corrosion and expand the life of the steel trash receptacle (can be upgraded to aluminium (ITEM #1206A-L) for an additional charge). **DOGIPOT®** offers Product Maintenance Paint to help cover any paint chips which may occur in the powder coating during the life of the product.

7. ENJOY WATCHING PET OWNERS PICK UP AFTER THEIR DOGS!

The Smart Solution to Dog Pollution.

800.364.7681

www.DOGIPOT.com

DOGIPOT® PET STATION (ITEM #1003-L)

SPECIFICATION, INSTALLATION AND OPERATION SHEET

(A) DOGIPOT® PET SIGN (ITEM #1203 / 1204)

- H: 18" x W: 11.5"
- 14 gauge reflective aluminum
- Weight: 1.35 lbs.
- Forest green on white

(B) ALUMINUM DOGIPOT® JUNIOR BAG DISPENSER (ITEM #1002-2)

- H: 15'5" x W: 9.4" x D: 3.25"
- 12 gauge powder coated forest green aluminum
- Weight: 7 lbs.
- 400 bag capacity
- Two diamond shaped bag dispenser slots
- Front locking access panel
- Clearly posted instructions

(C) STEEL TRASH RECEPTACLE WITH LID (ITEM #1206-L)

- H: 23" x 11.5" diameter
- 16 gauge powder coated forest green steel
- Weight: 14.6 lbs.
- 10 gallon capacity with interior trash liner bag retainer bands
- Attached stainless steel hinged lid
- One (1) box 50 count **DOGIPOT®** Smart Liner Trash Bags[™] (ITEM #1404) included (5 lbs.)

(D) TELESCOPIC GALVANIZED STEEL MOUNTING POST (ITEM #1301-P)

- 2" x 2" x 8'
- 11 gauge galvanized steel
- Weight: 15 lbs.

TOTAL HEIGHT FROM ABOVE GROUND:

• 6'.6"

SPACE BETWEEN DISPENSER AND SIGN:

• 1.0"

SPACE BETWEEN RECEPTACLE AND DISPENSER:

• 12.5"


SPACE BETWEEN GROUND AND RECEPTACLE:

• 8.0"

HOLE:

- D: 18.0" x W: 8.0"
- Fill with 40 lbs. "ready to use" cement

TOTAL SHIP WEIGHT: 45 LBS. (MOUNTING HARDWARE INCLUDED)



LEASH AND CLEAN

UP AFTER