

## **A-LINE LED BULB OPTIONS**

		Bulb Style	ltem	Package	Watts	Equivalent Watts	Lumens	Color	Hours	Base Type	Dimmable
		A15	168050	EA	5.5	40	450	3000°K	25,000	Medium	$\checkmark$
		A19	161185	EA	5.5	40	450	2700°K	25,000	Medium	$\checkmark$
A15		A19	168000	4/PK	9	60	800	2700°K	10,000	Medium	×
		A19	161230	EA	6	40	450	3000°K	12,000	Medium	×
		A19	161232	EA	9	60	800	3000°K	12,000	Medium	×
	A19	A19	161234	EA	11	75	1100	3000°K	12,000	Medium	×
	New	A19	168010	100/CS	10	60	800	2700°K	15,000	Medium	×
	New	A19	168012	100/CS	10	60	800	4000°K	15,000	Medium	×
A19 GU24 BASE		A19	161187	EA	9	60	800	5000°K	25,000	Medium	$\checkmark$
		A19	161240	EA	9	60	800	2700°K	25,000	GU24	$\checkmark$

## **OTHER LED** SHAPES AVAILABLE CHECK OUR CATALOG OR WEBSITE





FLOOD

TORPEDO

**f** 

GLOBE



R20 / R40 BR30 / BR40







PAR20 / PAR38

OMNI-DIRECTIONAL

## SATCO" NUVO

**MR16** 

## **Choosing Color Temperature**

www.ChadwellSupply.com | 888.341.2423 | (Esp.) 888.341.7330 | (Fax) 866.206.5581

www.satco.com

9/17 SA1285/

COLOR TEMPERATURE SCALE											
Soft V	Vhite	Brigh	t White	Natural Light							
2700K	3000K	3500K	4100K	5000K	7500K						
Warm 2700K is invit warm, friendl and relaxing.	y com	<b>tral</b> DK is inviting, fortable relaxing.	<b>Cool</b> 4100K is effic clean and organized.	cient, 500 refi	Daylight t, 5000K is exacting, refreshing, bright and alert.						
• Homes • Restaurants		owrooms ception	<ul> <li>Offices</li> <li>Hospitals</li> <li>Conference</li> </ul>	• Je	• Galleries • Jewelry displays						



